Carl-Cranz-Gesellschaft e.V.

Gesellschaft für technisch-wissenschaftliche Weiterbildung









Sensor-Datenfusion

Gintautas Palubinskas

German Aerospace Center (DLR)
Remote Sensing Technology Institute
Oberpfaffenhofen, Germany

Optical/SAR Data Fusion: Challenge

Optical/SAR Data Fusion: Challenge

WV-1

Optical/SAR Data Fusion

Motivation: Need for new and high quality products

- Why? Complementary nature of sources
- How?
  - Learn (understand) semantic relationships between objects
  - Develop methodology

Data Fusion: Definition

Data fusion is a formal framework in which are expressed the means and tools for the alliance of data originating from different sources.

It aims at obtaining information of greater quality; the exact definition of 'greater quality' will depend upon the application [1]

Data fusion is application dependent

[1] Wald L., 1999. Some terms of reference in data fusion. **IEEE Transactions on Geosciences and Remote Sensing**, 37(3), 1190-1193

Content

- Data fusion concept
- Data pre-processing
  - General fusion framework GFF
  - Orthogonal acquisition geometry
  - Ortho-rectification DEM/DSM
- Data fusion framework INFOFUSE
- Examples for optical/SAR classification
- Simulation of images
- Change detection
- Conclusions and outlook

Data Fusion: Concept



Processing chain



Processing chain II

WISSEN SCHAFFT ZUKUNFT

Pre-processing

- Orthogonal acquisition geometry
  - to minimize displacement effects [6]
- Ortho-rectification
  - DEM/DSM [7]
  - optical data enhancement using TS-X GCPs [2]
- Co-registration of optical/SAR data
  - using mutual information [3]
- Pan-sharpening of multi-spectral and panchromatic optical data
  - General Fusion Framework [4, 5]
- De-speckling of SAR imagery
- Simulation of SAR data (layover, shadow) [10]

Feature Extraction

- Gabor texture

Classification/Mapping

- INFOFUSE framework [8]

Change Detection

- using DSM and SAR simulation

Pan-sharpening

Pre-processing

- Orthogonal acquisition geometry
  - to minimize displacement effects [6]
- Ortho-rectification
  - DEM/DSM [7]
  - optical data enhancement using TS-X GCPs [2]
- Co-registration of optical/SAR data
  - using mutual information [3]
- Pan-sharpening of multi-spectral and panchromatic optical data
  - General Fusion Framework [4, 5]
- De-speckling of SAR imagery
- Simulation of SAR data (layover, shadow) [10]

Feature Extraction

- Gabor texture

Classification/Mapping

- INFOFUSE framework [8]

Change Detection

- using DSM and SAR simulation

Pan-sharpening

Input

Low resolution image (multispectral, hyperspectral, …)
High resolution image (panchromatic, SAR, …)

Aim

Include spatial information from high resolution image while preserving spectral properties of low resolution image

General Fusion Framework GFF

Method

Interpolation $msi = \mathrm{I}(ms)$

Fusion $msf = \mathrm{F}(msi, pan)$

Histogram matching $msf = \mathrm{H}(msf, ms)$

Spectral Fusion SF

How?

Add **only** high frequency information from high resolution image to low resolution image

Solution [4]

Fourier/spectral domain

Interpolation and fusion in one step

[4] Palubinskas, G. and Reinartz, P., 2011. Multi-resolution, multi-sensor image fusion: general fusion framework, **Proc. of Joint Urban Remote Sensing Event JURSE**, 11-13 April, 2011, Munich, Germany, IEEE, 313-316.

Spectral Fusion SF



Spectral Fusion SF

Fourier transform

$$MS = \mathrm{FFT}(ms)$$

$$PAN = \mathrm{FFT}(pan)$$

Zero padding and windowing

$$MSI = \mathrm{ZP}(W \cdot MS)$$

Frequency addition

$$MSF = MSI + PAN \cdot HPF$$

$$MSF = MSI + PAN \cdot (1 - LPF)$$

Inverse Fourier transform

$$msf = FFT^{-1}(MSF)$$

Spectral Fusion SF

Signal domain $$msf = msi + pan * hpf$$

where $$hpf = FFT^{-1}(HPF)$$

or $$msf = msi + pan - pan * lpf$$

[5] J. Hill, C. Diemer, O. Stover, and T. Udelhoven, 1999. A local correlation approach for the fusion of remote sensing data with different spatial resolution in foresty applications, **Proc. of Int. Archives of Photogrammetry and Remote Sensing**, Valladolid, Spain, June 3-4. 1999, Vol. 32, No. Part 7-4-3 W6, pp. 167–174.

WV-2 pan-sharpening (München)

WISSEN SCHAFFT ZUKUNFT

Original

WV-2 pan-sharpening (München)

WISSEN SCHAFFT ZUKUNFT

Fused

TS-X Radar-sharpening (München)

WISSEN SCHAFFT ZUKUNFT

WV-1

WV-1

rg

az

TS-X Radar-sharpening (München)

WISSEN SCHAFFT ZUKUNFT

Fused

WV-1

rg

az

TS-X

rg

az

TS-X Radar-sharpening (München)

TS-X

TS-X

rg

az

Orthogonal acquisition geometry

Pre-processing

- Orthogonal acquisition geometry
  - to minimize displacement effects [6]
- Ortho-rectification
  - DEM/DSM [7]
  - optical data enhancement using TS-X GCPs [2]
- Co-registration of optical/SAR data
  - using mutual information [3]
- Pan-sharpening of multi-spectral and panchromatic optical data
  - General Fusion Framework [4, 5]
- De-speckling of SAR imagery
- Simulation of SAR data (layover, shadow) [10]

Feature Extraction

- Gabor texture

Classification/Mapping

- INFOFUSE framework [8]

Change Detection

- using DSM and SAR simulation

3D Object height



Orthogonal acquisition geometry





[6] Palubinskas, G., Reinartz, P. and Bamler, R., 2010. Image acquisition geometry analysis for the fusion of optical and radar remote sensing data. **International Journal of Image and Data Fusion**, 1(3), 271-282

Two pairs of Optical/SAR acquisition

IKONOS2



TS-X ascending

WV-1



TS-X descending

Buildings: Example1

WV-2

Buildings: Example1



Buildings: Example2



Buildings: Example2



Ortho-rectification

WISSEN SCHAFFT ZUKUNFT

Pre-processing

- Orthogonal acquisition geometry
  - to minimize displacement effects [6]
- Ortho-rectification
  - DEM/DSM [7]
  - optical data enhancement using TS-X GCPs [2]
- Co-registration of optical/SAR data
  - using mutual information [3]
- Pan-sharpening of multi-spectral and panchromatic optical data
  - General Fusion Framework [4, 5]
- De-speckling of SAR imagery
- Simulation of SAR data (layover, shadow) [10]

Feature Extraction

- Gabor texture

Classification/Mapping

- INFOFUSE framework [8]

Change Detection

- using DSM and SAR simulation

Analysis of Building Signature



Classification

Pre-processing

- Orthogonal acquisition geometry
  - to minimize displacement effects [6]
- Ortho-rectification
  - DEM/DSM [7]
  - optical data enhancement using TS-X GCPs [2]
- Co-registration of optical/SAR data
  - using mutual information [3]
- Pan-sharpening of multi-spectral and panchromatic optical data
  - General Fusion Framework [4, 5]
- De-speckling of SAR imagery
- Simulation of SAR data (layover, shadow) [10]

Feature Extraction

- Gabor texture

Classification/Mapping

- INFOFUSE framework

Change Detection

- using DSM and SAR simulation [8]

Data fusion framework INFOFUSE



[8] Palubinskas, G. and Datcu, M., 2008. Information fusion approach for the data classification: an example for ERS-1/2 InSAR data. **International Journal of Remote Sensing**, 29(16), 4689-4703.

Data fusion requirements and solutions

Requirements

- to follow consensus theory [9]
- Data non-commensurability: to work with different input data (e.g. nature and statistics of optical and SAR)
- Arbitrary number of data sources
- Aggregation method to be able to use arbitrary number of calculated input features
- Acceptable complexity

Solutions

- Data fission is employed (to calculate exhaustive feature set). Quasi-full characterization of classes
- Feature representation on a finite predefined domain (e.g. numbers of a range). Reduce of data size
- Neural Networks, Bayesian networks, or Graphical models

[9] Benediktsson, J., Sveinsson, J., and Swain, P., 1997. Hybrid consensus theoretic classification, **IEEE Transactions on Geoscience and Remote Sensing**, 35(4), 833–843.

Feature aggregator selection

Feature Aggregator	Advantages	Disadvantages
Neural Network	Acceptable training time Variety of methods for learning High accuracy of classification	Overtraining
Bayesian Network	Knowledge representation in probabilistic way Proper configuration using expert knowledge	High training/classification time
Graphical model	Knowledge representation in probabilistic way (assuming multi-nominal distributions) Proper configuration using expert knowledge (compare to neural network)	High training/classification time No practical methods for structure learning

Data characteristics

Sensor Parameter	**TerraSAR-X**	**WorldView-2**
Image time (local)	7-Jun-2008 07:17:48	12-Jul-2010 10:30:17
Mode	Spotlight HS	Pan-sharpened VNIR bands
Look angle	49.45° Right	5.2° Left
Orbit	Descending	Descending
Polarization	Single, VV	
Product	EEC	L2A
Resolution gr x az (m)	1.0 x 1.14	0.5 x 0.5
Pixel spacing (m)	0.5	0.5
Radiometric resolution	16 bit	11 bit

Experiment 1

Urban area classification:

- Munich city
- 6 classes

Features:

- WV-2 VNIR (4 bands)
- TS-X Texture (Co-occurrence)

Fusion strategies:

- VNIR
- VNIR+SAR Texture

Urban area classification

Optical RGB image



INFOFUSE classification

Label	Classes/subclasses
Buildings	8 subclasses
Roads	2 subclasses
Water	1 class
Forest/Trees	1 class
Grass	1 class
Shadows	1 class

Input data:

- WorldView-2 multispectral (VNIR range)
- TerraSAR-X single polarization band

Haralick texture features

Urban area classification zoom





SAR data allow to reduce errors in building/road separation





Confusion matrices

WISSEN SCHAFFT ZUKUNFT

Class	*Water*	*Grass*	*Trees*	*Buildings*	*Road*	*Shadow*
Water	100.00	0	0	0	0	0
Grass	0	85.47	0	0	0	0
Trees	0	14.53	100.00	0	0	0
Buildings	0	0	0	**60.05**	**42.25**	4.72
Road	0	0	0	**39.95**	**57.75**	0
Shadow	0	0	0	0	0	95.28
Total	100.00	100.00	100.00	100.00	100.00	100.00

INFOFUSE Multispectral (VNIR)
Overall Accuracy: 70.95%
Kappa Coefficient: 0.6059

Class	*Water*	*Grass*	*Trees*	*Buildings*	*Road*	*Shadow*
Water	100.00	0	0	0	0	0
Grass	0	98.20	0	0	0	0
Trees	0	1.80	98.90	0	0	0
Buildings	0	0	0	**96.36**	**3.91**	0.47
Road	0	0	1.10	**3.64**	**96.06**	0
Shadow	0	0	0	0	0	99.53
Total	100.00	100.00	100.00	100.00	100.00	100.00

INFOFUSE Multispectral (VNIR)+SAR
Overall Accuracy: 97.19%
Kappa Coefficient: 0.9613

Experiment 2

Urban area classification:

- Munich city
- 23 classes

Features:

- WV-2 (8 bands), Red Band Texture-Gabor (6 orientations, 4 sine modulations, 2 sigma sizes)
- TS-X Texture-Gabor (6 orientations, 4 sine modulations, 2 sigma sizes)
- DSM (Generated from WV-2 panchromatic stereo pair)

Fusion strategies:

- Multispectral, DSM (9 features),
- Texture SAR, Texture optical, DSM (97 features),
- Multispectral, Texture SAR, Texture optical (104 features),
- **Multispectral, Texture SAR, Texture optical and DSM (105 features)**

Classes

23 classes were defined:

- 1. Water
- 2. Forest/Trees
- 3. Grass/Low vegetation
- 4. Bare soil
- 5. Construction site
- 6. Swimming pool
- 7. Asphalt road
- 8. Concrete road
- 9. Football field
- 10. Tennis field
- 11. Green house
- 12. Rail road
- 13. Tram line
- 14. Cemetery
- 15. Parking/car
- 16. Shadow
- 17. Red roofing tiles
- 18. Grey roofing tiles
- 19. Dark roofing tiles
- 20. Roofing concrete
- 21. Vegetation roof
- 22. Zinc roof
- 23. Roofing copper

Ground truth

- ATKIS vector map (Landesamt für Vermessung und Geoinformation)
- Material vector data (Dr. Wieke Heldens)

Classification accuracy

Maximum likelihood (does not follow consensus theory)		
	OVA, %	Kappa
Multispectral, DSM (9 features)	85.4841	0.8409
Texture, DSM (97 features)	60.5719	0.5666
Multispectral, Texture (104 features)	81.4288	0.7932
Multispectral, Texture, and DSM (105 features)	82.1923	0.8019
Neural Network (1 hidden layer, 40 neurons for 97, 104, or 105 features, 8 neurons for 9 features)		
	OVA, %	Kappa
Multispectral, DSM (9 features)	85.6575	0.8426
Texture, DSM (97 features)	60.8644	0.5643
Multispectral, Texture (104 features)	82.6471	0.8076
Multispectral, Texture, and DSM (105 features)	87.0697	0.8566
INFOFUSE (based on Neural Network, 1 hidden layer, 40 neurons for 97, 104, or 105 features, 9 neurons for 8 features) (50 clusters for each feature)		
	OVA, %	Kappa
Multispectral, DSM (9 features)	85.1835	0.8360
Texture, DSM (97 features)	71.8699	0.6906
Multispectral, Texture (104 features)	88.8692	0.8768
Multispectral, Texture, and DSM (105 features)	**90.1092**	**0.8907**

Classification accuracy



Classification map 1



- water
- forest
- grass
- bare_soil
- construction
- pool
- road_asphalt
- football
- tennis
- green_house
- rail
- tram
- cemetery
- parking/car
- shadow
- concrete
- red_roofing_tiles
- concrete_roof
- vegetation_roof
- dark_roofing_tiles
- zink_roof
- roofing_copper
- grey_roofing_tiles

Classification map 2



- water
- forest
- grass
- bare_soil
- construction
- pool
- road_asphalt
- football
- tennis
- green_house
- rail
- tram
- cemetery
- parking/car
- shadow
- concrete
- red_roofing_tiles
- concrete_roof
- vegetation_roof
- dark_roofing_tiles
- zink_roof
- roofing_copper
- grey_roofing_tiles

Classification map 3



Influence of data sources on classification

Confused classes		Sensor or feature influence for proper classification
Class 1	Class 2	Sensor/Feature
Road	Building	DSM
Rail road/Tram road	Road	SAR Texture
Rail road	Tram road	SAR Texture
Bare soil	Construction site	SAR Texture
Football field	Grass/Low vegetation	SAR Texture, Multispectral
Parking/car	Road	Texture on optical data
Cemetery	Grass/Low vegetation	SAR Texture
Green house	Road	SAR Texture, Multispectral

Simulation

Pre-processing

- Orthogonal acquisition geometry
  - to minimize displacement effects [6]
- Ortho-rectification
  - DEM/DSM [7]
  - optical data enhancement using TS-X GCPs [2]
- Co-registration of optical/SAR data
  - using mutual information [3]
- Pan-sharpening of multi-spectral and panchromatic optical data
  - General Fusion Framework [4, 5]
- De-speckling of SAR imagery
- Simulation of SAR data (layover, shadow) [10]

Feature Extraction

- Gabor texture

Classification/Mapping

- INFOFUSE framework

Change Detection

- using DSM and SAR simulation

Laser DSM



Horizontal resolution: 1m
vertical resolution: 0.1m

Simulation optical/SAR images



Simulated optical image

WV-1 image



TS-X image



Simulated SAR image

Single building extraction from DSM

1.FK_LS

2.FK_haus

3.FK_road

4.FK_road_median

5.FK_road_median_idw

6.FK_haus_G1m

7.FK_haus_G1

8.FK_haus_G1r



Single building model



DEM + single building model

Single building simulation in optical image



Single building simulation in SAR image



azimuth

range

Line extraction in TS-X image



Line extraction in simulated image



Line extraction for single building



Extracted lines

TSX image

Simulated image

image





Extracted line features





Lines matching



Lines from TSX (highlighted in colour)
Lines from simulated image (white)

Scene interpretation



TSX (cyan), Simulated image (red)

Single building interpretation



TSX (cyan), reflection and shadow area of single building model (red)

Simulation

Pre-processing

- Orthogonal acquisition geometry
  - to minimize displacement effects [6]
- Ortho-rectification
  - DEM/DSM [7]
  - optical data enhancement using TS-X GCPs [2]
- Co-registration of optical/SAR data
  - using mutual information [3]
- Pan-sharpening of multi-spectral and panchromatic optical data
  - General Fusion Framework [4, 5]
- De-speckling of SAR imagery
- Simulation of SAR data (layover, shadow) [10]

Feature Extraction

- Gabor texture

Classification/Mapping

- INFOFUSE framework [8]

Change Detection

- using DSM and SAR simulation

Change Detection using Simulation

WISSEN SCHAFFT ZUKUNFT

- 1.TSX image
- 2. Coregist. geocoded simulated image
- 3. Shadow of simu. Img.
- 4. Corresponding mask of TSX image
- 5. (4 after thresholding)
- 6. (5 after median filter)
- 7. Reference:3D change result [Tian 2010]



Conclusions

- What is needed for successful optical/SAR data fusion especially for VHR and urban area?
  - Data acquisition planning
    - Different SAR orbits (ascending, descending)
    - Different SAR incidence angles
    - Multi-temporal aspect
  - Data preparation
    - Accurate Digital Surface Model DSM (including buildings etc)
    - Orthorectification excluding layover and shadow areas (e.g. simulation), using high SAR location accuracy
    - Co-registration multi-sensor data (e.g. mutual information)
    - Feature extraction (e.g. SAR texture in slant geometry) and selection

Outlook

- Which DSM quality is required or sufficient?
- Unmixing layover areas using multi-temporal SAR acquisitions
- Filling SAR shadow areas using optical acquisitions
- How many data are needed to obtain gapless orthoimage?
- Which data fusion method?
- How to assess quality?
- Applications:
  - Classification
  - Change Detection

References

[1] Wald L., 1999. Some terms of reference in data fusion. **IEEE Transactions on Geosciences and Remote Sensing**, 37(3), 1190-1193

[2] Palubinskas, Gintautas**,** 2013. Fast, simple and good pan-sharpening method, **Journal of Applied Remote Sensing**, vol. 7, no. 1, 073526, pp. 1-12, August 09, 2013.

[3] Reinartz, P., Müller, R., Schwind, P., Suri, S. and Bamler, R., 2011. Orthorectification of VHR optical satellite data exploiting the geometric accuracy of TerraSAR-X data. **ISPRS Journal of Photogrammetry and Remote Sensing**, 66, 124-132.

[4] Palubinskas, Gintautas; Makarau, Aliaksei and Reinartz, Peter**,** 2012. Information extraction using optical and radar remote sensing data fusion, **Proc. of ASPRS Annual Conference**, 19-23 March, 2012, Sacramento, California, USA, ASPRS, 9 pages.

[5] Suri, S. and Reinartz, P., 2010. Mutual-Information-Based Registration of TerraSAR-X and Ikonos Imagery in Urban Areas. **IEEE Transactions on Geoscience and Remote Sensing** 48(2), 939-949.

[6] Palubinskas, Gintautas and Reinartz, P., 2011. Multi-resolution, multi-sensor image fusion: general fusion framework, **Proc. of Joint Urban Remote Sensing Event JURSE**, 11-13 April, 2011, Munich, Germany, IEEE, 313-316.

[7] J. Hill, C. Diemer, O. Stover, and T. Udelhoven, 1999. A local correlation approach for the fusion of remote sensing data with different spatial resolution in foresty applications, **Proc. of Int. Archives of Photogrammetry and Remote Sensing**, Valladolid, Spain, June 3-4. 1999, Vol. 32, No. Part 7-4-3 W6, pp. 167–174.

[8] Palubinskas, Gintautas; Reinartz, P. and Bamler, R., 2010. Image acquisition geometry analysis for the fusion of optical and radar remote sensing data. **International Journal of Image and Data Fusion**, 1(3), 271-282.

[9] Palubinskas, Gintautas and Datcu, M., 2008. Information fusion approach for the data classification: an example for ERS-1/2 InSAR data. **International Journal of Remote Sensing**, 29(16), 4689-4703.

[10] Makarau, Aliaksei; Palubinskas, Gintautas and Reinartz, Peter, 2011. Multi-sensor data fusion for urban area classification, **Proc. of Joint Urban Remote Sensing Event JURSE**, 11-13 April, 2011, Munich, Germany, Stilla U, Gamba P, Juergens C, Maktav D (eds.), IEEE, 21-24.

References

[11] Tao, J., Palubinskas, Gintautas; Auer, S., and Reinartz, P., 2011. Interpretation of SAR images in urban areas using simulated optical and radar images, **Proc. of Joint Urban Remote Sensing Event JURSE**, 11-13 April, 2011, Munich, Germany, 41-44.

[12] Benediktsson, J., Sveinsson, J., and Swain, P., 1997. Hybrid consensus theoretic classification, **IEEE Transactions on Geoscience and Remote Sensing**, 35(4), 833–843.

[13] Palubinskas, Gintautas**,** 2012**.** How to fuse optical and radar imagery?, **Proc. of IGARSS**, 22-27 July, 2012, Munich, Germany, IEEE, pp. 2171-2174.

[14] Makarau, Aliaksei; Palubinskas, Gintautas and Reinartz, Peter, 2012. Analysis and selection of pan-sharpening assessment measures, **Journal of Applied Remote Sensing**, vol. 6, no. 063548, pp. 1-20.

[15] Makarau, Aliaksei; Palubinskas, Gintautas and Reinartz, Peter, 2013**.** Alphabet-based multisensory data fusion and classification using factor graphs, **IEEE Journal of Selected Topics in Applied Earth Observations and Remote Sensing**, vol. 6, no. 2, pp. 969-990.

[16] Makarau, Aliaksei; Palubinskas, Gintautas and Reinartz, Peter, 2012. Selection of numerical measures for pan-sharpering assessment, **Proc. of IGARSS**, 22-27 July, 2012, Munich, Germany, IEEE, pp. 2264-2267.

[17] Palubinskas, Gintautas; Makarau, Aliaksei and Reinartz, Peter, 2011. Multi-sensor remote sensing information fusion for urban area classification and change detection, **Proc. of SPIE Defence, Security, and Sensing Symposium**, 25-29 April, 2011, Orlando, USA, vol. 8064, 80640F, 10 pages

[18] Makarau, Aliaksei; Palubinskas, Gintautas and Reinartz, Peter, 2012. Factor graph models for multisensory data fusion: from low-level features to high level interpretation, **Proc. of IGARSS**, 22-27 July, 2012, Munich, Germany, IEEE, pp. 162-165.

[19] Palubinskas, Gintautas; Makarau, Aliaksei and Tao, Junyi, 2011. Fusion of optical and radar data for the extraction of higher quality information**, 4th TS-X Science Team Meeting**, 14-16 February 2011, DLR, Oberpfaffenhofen, Germany, 9 pages.

[20] Makarau, Aliaksei; Palubinskas, Gintautas and Reinartz, Peter, 2011. Classification accuracy increase using multisensor data, **Proc. of ISPRS Hannover Workshop 2011** - High Resolution Earth Imaging for Geospatial Information, 14-17 June, 2011, Hannover, Germany, ISPRS, vol. XXXVIII-1-4-7, part W5, 6 pages.

References

[21] Makarau, Aliaksei; Palubinskas, Gintautas and Reinartz, Peter, 2011**.** Discrete graphical models for alphabet-based multisensory data fusion and classification, **Proc. of International Symposium on Image and Data Fusion**, 9-11 August, 2011, Tengchong, China, 4 pages.

[22] Palubinskas, Gintautas and Reinartz, Peter, 2010. Fusion of optical and radar remote sensing data: Munich city example, In**: ISPRS Technical Commision VII Symposium** - 100 Years ISPRS, 5-7 July, 2010, Vienna, Austria, Wagner, W., Szekely, B. (eds.), IAPRS, Vol. XXXVIII, Part 7A, pages 181-186.

[23] Tao, Junyi; Palubinskas, Gintautas and Reinartz, Peter, 2011. Automatic interpretation of high resolution SAR images: first results of SAR image simulation for single buildings, **Proc. of ISPRS Hannover Workshop 2011** - High Resolution Earth Imaging for Geospatial Information, 14-17 June, 2011, Hannover, Germany, ISPRS, vol. XXXVIII-1-4-7, part W5, 6 pages.

[24] Tao, Junyi; Palubinskas, Gintautas and Reinartz, Peter, 2011. Simulation based change detection between DSM and high resolution SAR image, **Proc. of International Symposium on Image and Data Fusion**, 9-11 August, 2011, Tengchong, China, 4 pages.

[25] Tao, Junyi; Auer, Stefan; Palubinskas, Gintautas; Reinartz, Peter and Bamler, Richard, 2013. Automatic SAR simulation technique for object identification in complex urban scenarios, **IEEE Journal of Selected Topics in Applied Earth Observations and Remote Sensing**